


BOSCHE
WEIGHING SYSTEMS

Platform scale *TP C*









Functions & features

- Verifiable version to accuracy class III
- Stainless steel platform sizes:
  300 x 400 | 400 x 400 | 400 x 500 | 500 x 600 | 600 x 600 | 600 x 800 mm
- Weighing capacities: 30 kg / 60 kg / 150 kg / 300 kg
- Maintenance-free, wear-free weighing technology
- MCI-t (verifiable) and GTC-T (non-verifiable) weighing indicators in aluminium housings
- Adjustable backlighting
- Large backlit 60 mm LCD display with 50 mm-high digits
- Alibi memory with time and date
- Simple, user-friendly operation
- Parts counting function
- Three displays: piece weight – piece count – actual weight
- Optional 400 or 600 mm-high stand to raise the weighing indicator
- Verifiable version available on request

Installation

Four rubber feet ensure safe, stable positioning of the platform scale. Adjustable levelling feet and a spirit level help align the scale. It is ready for use as soon as it has been installed.
An optional transport trolley is available for the platform scale.

+49 (0) 5491.999.689.0
www.bosche.eu

BOSCHE
WEIGHING SYSTEMS

Platform scale *TP C*

The TP-C digital platform scale is designed for daily use in industry, commerce and logistics. From weighing parcels and components to picking small parts, the BOSCHE platform counting scale handles a wide range of weighing and counting tasks. Its detachable weighing indicator allows flexible use and positioning.

Combined with the basic weighing indicator, the platform is designed for verifiable counting applications with the MCI indicator and non-verifiable applications with the GTC indicator. Clearly arranged keys ensure simple operation. Weight is shown on the main display, while piece count and piece weight appear on two separate auxiliary displays.

Its lightweight construction and optional transport trolley also allow mobile use.


Construction
The weighing plate is made of stainless steel, with a robust base of high-quality die-cast aluminium. The load is transferred directly to a precise strain gauge load cell. The construction's high load-bearing capacity and rigidity help ensure a long service life. The weighing platform is connected to the indicator by a 1.8 m cable. The indicator can be placed on a table or mounted on a wall using an optional wall bracket.

Power supply and interfaces
The platform scale is supplied for mains operation as standard, with a mains plug included. An optional rechargeable battery allows operation without a mains supply.

The serial RS-232 interface supports bidirectional transfer of weight data to a PC, printer or remote display. Data cables, a remote display and a printer are available as accessories.

Accessories

Item	Description
Stand	Stainless steel stand to raise the weighing indicator
Battery	Internal rechargeable battery with up to 15 hours of operation
E 50	Verification charge up to 50 kg
E 350	Verification charge up to 350 kg
Second RS 232 data interface	Serial interface for transmitting measurement data to a printer, PC, etc.



+49 (0) 5491.999.689.0
www.bosche.eu

BOSCHE GmbH & Co. KG
Reselager Rieden 3
49401 Damme