BOSCHE
WÄGETECHNIK

Cattle Crush with Scale RTW 2513



Functions & Features

- Hot-dip galvanised steel construction with integrated scale
- Entrance sliding door; Priefert headgate at the exit
- Non-slip chequer plate floor, raised at the sides
- Outer dimensions (L × W): 250 × 130 cm; cage height: 198 cm
- Individually removable side bars for targeted access
- Internal platform dimensions: 218 × 80 cm
- Passage height: 171 cm; passage width: 75 cm
- Weight with cage: 430 kg
- **SWE weighing indicator functions:**
  - HIGH-LOW-GO: checkweighing with adjustable minimum and maximum weight limits.
  - Animal weighing: calculates a stable average for restless animals to provide accurate weight readings.
  - Zero and tare functions: manual tare, gross / net.
  - Totalising: up to 9,999 weighings.





+49 (0) 5491.999.689.0
www.bosche.eu

BOSCHE
WÄGETECHNIK

Cattle Crush with Scale RTW 2513

Weigh, restrain and treat
The RTW 2513 combines a cattle crush with a livestock scale. With a capacity of 1,500 kg, a readability of 1 kg and four integrated K30S-C3-2000 load cells, it is ideal for monitoring the weight of cattle and bulls. The hot-dip galvanised construction is designed for daily use in barns and farmyards.

The Priefert headgate secures the head with an automatic latch and animal-friendly catch bars, without manual adjustment of the neck width. The operating lever can be fitted on the left or right for manual or automatic catching. Individually removable side bars provide targeted access for injections, treatments and examinations.

The optional SWE features a backlit LCD with 30 mm digits, an IP54 aluminium housing and four function keys. Its animal weighing program calculates stable averages for restless animals. Power is supplied by a 100–240 V mains adapter; the optional Li-ion battery provides up to 30 hours of operation, or 18 hours with the backlight on.

Accessories and versions
Optional data storage records weights with date and time for USB transfer and analysis in MS Excel. A version with an exit sliding door instead of a headgate is available on request. Price and delivery time on request.

Applications

Animals: Cattle, bulls, cows, young stock and calves
Operations: Farms, fattening and breeding operations, and veterinary practices
Uses: Regular weight monitoring, injections, treatments and veterinary examinations

SWE weighing indicator

The SWE weighing indicator is intended for use with the RTW 2513 cattle crush.
Its dedicated animal weighing program delivers stable readings even with restless animals.

- Large backlit LCD with 30 mm digits
- Robust aluminium housing, IP54 protection
- Moisture-resistant membrane keypad with 4 function keys
- Animal weighing: calculates a stable average for moving loads to provide accurate weight readings
- HIGH-LOW-GO: checkweighing with adjustable minimum and maximum weight limits
- Zero and tare functions: manual tare, gross / net
- Totalising: up to 9,999 weighings
- Peak / Hold: peak value and hold functions
- Power supply: 100–240 V mains adapter; optional built-in Li-ion battery for up to 30 h of operation (18 h with backlight)
- Optional: RS-232 or USB interface



Updated: 11/26

+49 (0) 5491.999.689.0
www.bosche.eu

BOSCHE GmbH & Co. KG
Reselager Rieden 3
49401 Damme